

L5 ANSWER 475 OF 575 CA COPYRIGHT 2004 ACS on STN

AN 94:144428 CA

ED Entered STN: 12 May 1984

TI Plastering mortar composition

PA Tokuyama Soda Co., Ltd., Japan

SO Jpn. Kokai Tokkyo Koho, 5 pp.

CODEN: JKXXAF

DT Patent

LA Japanese

IC C04B013-00

CC 58-3 (Cement and Concrete Products)

FAN.CNT 1

| | PATENT NO. | KIND | DATE | APPLICATION NO. | DATE |
|------|---------------|------|----------|-----------------|----------|
| PI | JP 55130847 | A2 | 19801011 | JP 1979-38339 | 19790402 |
| | JP 58057386 | B4 | 19831220 | | |
| PRAI | JP 1979-38339 | | 19790402 | | |

AB The plastering mortar contains cement 100, fly ash 10-50, gypsum 2-24 (as SO₃), water -granulated slag 100-300, sulfonate 0.4-4 parts, and cellulose ether in an amt. (C) of (E-1)/10 .ltoreq. C .ltoreq. (E + 1)/10, where E is the sulfonate content. Thus, a mortar contg. cement 100, fly ash 40, gypsum 10, water -granulated slag 150, Na lignosulfonate [8061-51-6] 0.75, and methylcellulose [9004-67-5] 0.06 part was coated on a concrete plate at 5 mm thickness and cured. The coating had no cracking or efflorescence even after 3 mo.

ST plastering mortar

IT Mortar

Plaster

(from cement and slag, contg. sodium lignosulfonate and Me cellulose)